

## BATTERY CELL COMPARISON FOR ELECTRIC VEHICLES USING SCILAB

Hrushikesh Anil Chari<sup>1\*</sup>, Dr. R S Katikar<sup>2</sup>

<sup>1,2</sup>Deptt. of Prod. Engg. Sinhgad College of Engineering, Pune

### Abstract

The Battery Pack is an integral part of an electric vehicle. All the performance parameters of an electric vehicle largely depend on the specification of the battery pack. In recent years, there has been a tremendous advancement in battery cell technology, which has resulted in the betterment of the specification of battery cells. Due to these developments, we can foresee electric vehicles as a sustainable and environment-friendly mode of transport. This paper will describe the critical consideration parameters for the battery cell selection process. The research paper will also explain the comparison of battery cells with the help of Scilab programming for getting accurate results.

**Keywords:** Scilab, Energy Consumption, Cell Data, Parameter Calculation, Scinotes;

### 1. Introduction

Electric vehicles have established themselves as an appropriate alternative for conventional gasoline-powered engines due to their environment-friendly and sustainable mode of transport. It has resulted in tremendous research and development of various systems in electric vehicles. The traction Battery Pack is an integral part of the electric vehicle powertrain. The performance of an electric vehicle extensively depends upon the battery pack parameters. With the new inventions of battery chemistries, we can witness a wide range of parameters of battery cells. Thus, the selection process of battery cells becomes a bit difficult in choosing the correct trade-off between the parameters.

There are numerous methods and models for the selection process across various parameters. For an optimal design, it is necessary to have the best trade-off amongst the parameters. Mathematical modeling is one such tool that can help carry out such different and complex tasks with ease.

Today electric vehicles have many drawbacks associated with the battery pack as the range, charging duration, compactness. Such drawbacks can be solved by using an effective and efficient method for selecting the best-suited battery cell of the desired operation. The paper will be discussing one such method that can be effective and convenient for comparing various battery parameters for the desired application.

## 2. LITERATURE REVIEW

A report by Fengqi Chang has explained the influence of the number of parallel cells in a battery pack is evaluated in Monte-Carlo experiments.[1]

Dr. K.V. Vidyanandan in his report has provided an overview of Li-ion batteries, their limitations, safety concerns, and the emerging battery technologies to meet future requirements. [2]

The report by S. Tamilselvi describes a study of various battery models such as electrochemical models, mathematical models, circuit-oriented models, and combined models for different types of batteries. It also explains the advantages and drawbacks of these types of modeling. [3]

In his report by Hrushikesh Chari has proposed a mathematical method for calculating the total energy consumption for electric scooters and the battery cell selection process using the features of SCILAB. [4]

It can be inferred from the literature reviewed that method used are lengthy and quite complicated and does not elaborate on the battery cell comparison methods.

This paper will explain the application of Scilab programming for the comparison of battery cells conveniently and effectively. For the comparison of the battery cells, some data will be used as a reference from the report by Hrushikesh Chari.

## 3. Overview of Battery Cell

### A. Battery Chemistries

There are various battery chemistries are used in electric vehicles, but all of them have distinct parameters. Below listed are a few common types of battery chemistries: -

- **Lithium-Ion Batteries:** The prominent type of battery used in electric cars is the lithium-ion battery. These batteries cells are used in most portable electronics, like mobile phones and computers. Lithium-ion batteries have a high power-to-weight ratio, high energy efficiency, and good high-temperature performance.
- **Nickel-Metal Hydride Batteries:** Nickel-metal hydride batteries are widely used in hybrid-electric vehicles but are also used successfully application in some all-electric vehicles. These batteries have a longer life cycle than lithium-ion or lead-acid batteries. The biggest issues with these batteries is their high cost, high self-discharge rate, and significant heat generation at high temperatures.
- **Lead-Acid Batteries:** Lead-acid batteries are only currently being used in electric vehicles to supplement auxiliary systems. These batteries are high-powered, economical, safe, and reliable, but they have short lifecycle and poor cold-temperature performance, it make them difficult to use in electric vehicles.
- **Ultracapacitors:** Ultracapacitors are not batteries, instead they store polarized liquid between an electrode and an electrolyte. As the liquid's surface area increases, the capacity for energy storage also increases.[6]

## B. Battery Parameters

The desired characteristics of a battery from electric vehicles are: for longer drive distances high specific energy, for good acceleration high specific power, high safety features, wide operating temperature range, for fast charging low internal resistance, for high instantaneous torque high peak current long life, and affordable price.[2]

Below listed are a few common battery parameters that must be considered while selecting the battery cells: -

- **Battery cell capacity:** The battery capacity represents the maximum amount of energy that can be extracted from the battery under certain specified conditions. It is expressed in ‘Amp-hr’
- **Battery cell nominal voltages:** The voltage of a battery is a basic characteristic of a battery, which is determined by the chemical reactions in the battery, the concentrations of the battery components, and the polarization of the battery. It is expressed in ‘Volts’
- **Energy Density – Gravimetric:** The gravimetric energy density *also called as* the specific energy of a battery is a measure of how much energy a battery contains in comparison to its weight, and is typically expressed in Watt-hours/kilogram (W-hr/kg).
- **Energy Density – Volumetric:** The volumetric energy density *also called as* the energy density of a battery is a measure of how much energy a battery contains in comparison to its volume and is expressed in Watt-hours/liter (W-hr/l)
- **Battery cell continuous current:** The maximum current at which the battery can be discharged continuously. It is expressed in ‘Amp’.
- **Battery cell peak current:** The peak current is the maximum amount of current that output is capable of sourcing for brief periods. It is expressed in ‘Amp’.[5]
- **C-rating:** The battery C rating is the measurement of the current at which a battery is charged and discharged.

EV batteries are *deep cycle* (DC) batteries. DC batteries have thicker positive electrode plates but have relatively less surface area available to take part in electrochemical reactions. They can be discharged down to 30-20% of SOC (state of charge) for over a thousand cycles.[2]

## 4. Methodology

As mentioned above to compare battery cells the data will be taken from “Mathematical modeling of the electric scooter battery pack using SCILAB” as the reference values for calculation. For the comparison of the battery cell, the predefined values are range=120km, voltage=60V, and energy consumption=30.3Wh/km. [4] The comparison of the cells will be carried out by analyzing the graphs generated by executing the code in SCInotes. The program can be segmented into three sections uploading cell data, calculating parameters, and plotting the graph.

Firstly, the shortlisted cell specification is to be filled in an excel file and saved in a folder. Figure 1 is the screenshot of the selected cells.

### A. Uploading Cell Data

After filling the battery cell specification in the excel file, it is saved in the required folder. Later by launching Scilab and opening SCInotes for writing the program. Firstly, the cell data is imported and it is been uploaded to the workspace for further calculation. Then, the values of the predefined values of range, voltage, and energy consumption are entered and the value for each variable is called as shown in figure 2.

	A	B	C	D	E	F
1	Manufacturer	LG	Sony	A&S Power	Samsung	Panasonic
2	Type	cylindrical	cylindrical	pouch	cylindrical	cylindrical
3	Model	INR18650HE4	US18650VTC6	AS1365132	INR18650-25R	NCR18650E
4	Length [m] (For cylindrical)	0.065	0.065	0	0.065	0.065
5	Diameter [m] (For cylindrical)	0.0185	0.0183	0	0.0183	0.0185
6	Height [m] (For prismatic)	0	0	0.132	0	0
7	Width [m] (For prismatic)	0	0	0.065	0	0
8	Thickness [m] (For prismatic)	0	0	0.013	0	0
9	Mass [kg]	0.047	0.046	0.25	0.0438	0.045
10	Capacity [Ah]	2.5	3.12	10	2.5	2.25
11	Voltage [V]	3.6	3.6	3.65	3.64	3.6
12	C-rate (cont.)	8	6.67	5	8	6.67
13	C-rate (peak)	14	11.67	10	14	11.67

Figure 1. Battery cell specification data import

```

0001 clear
0002clc
0003 sheets = readxls('celldata.xls');
0004 data = sheets(1);
0005
0006 c_no = size(data,"c")
0007
0008 //----- ENTER YOUR VALUES HERE -----
0009
0010 voltage = 60 //Enter maximum battery voltage
0011 range = 120 // Enter required Range
0012 energy_consumption = 30.3 //Enter average energy consumption from previous simulation [Wh/km] WLTC
0013
0014 //-----
0015
0016 /// Battery cell data
0017 bc_manufacturer = data (1, 2:6)
0018 bc_type = data (2, 2:6);
0019 bc_model = data (3, 2:6); // [m]
0020 bc_length = data (4, 2:6); // [m]
0021 bc_diameter = data (5, 2:6); // [m]
0022 bc_height = data (6, 2:6); // [m]
0023 bc_width = data (7, 2:6); // [m]
0024 bc_thickness = data (8, 2:6); // [m]
0025 bc_mass = data (9, 2:6); // [kg]
0026 bc_capacity = data (10, 2:6); // [Ah]
0027 bc_voltage = data (11, 2:6); // [V]
0028 bc_conductance = data (12, 2:6);
0029 bc_peakCrate = data (13, 2:6);
0030
    
```

Figure 2. Program for Uploading Cell Data

### B. Calculation

To generate the graphs for comparison, the calculation of the parameters is essential. The required formulas are written in the program with the necessary conditions. The table below shows the formulas used for the calculation.

TABLE I. Formulas for Parameter Calculation

Sr. No.	Parameter	Formula
1	Energy Density – Gravimetric [Wh/kg]	$\frac{\text{Battery cell energy [Wh]}}{\text{Battery cell mass [kg]}}$
2	Energy Density – Volumetric [Wh/ m <sup>3</sup> ]	$\frac{\text{Battery cell energy [Wh]}}{\text{Battery cell volume [m}^3\text{]}}$
3	Battery Pack Capacity [Ah]	$\text{No. of string} \times \text{Battery cell capacity [Ah]}$
4	Battery Pack Continuous Current [A]	$\text{Sting continous current [A]} \times \text{No. of strings in pack}$
5	Battery Pack Continuous Power [W]	$\text{Battery pack continous current [A]} \times \text{Battery pack voltage [V]}$
6	Battery Pack Energy [Wh]	$\text{No. of string} \times \text{Battery cell energy content [Wh]}$
7	Battery Pack Peak Current [A]	$\text{Sting peak current [A]} \times \text{No. of strings in pack}$
8	Battery Pack Peak Power [W]	$\text{Battery pack peak current [A]} \times \text{Battery pack voltage [V]}$
9	Battery Pack Volume (only cells) [m <sup>3</sup> ]	$\text{Total no. of cells} \times \text{Volume of each battey cell [kg]}$
10	Battery Pack Mass (only cells) [Kg]	$\text{Total no. of cells} \times \text{Mass of each battey cell [kg]}$
11	Total Number of Cells	$\text{No. of cells in string} \times \text{No. of strings}$

The figure 3 is the screenshot of the Scilab program, it is the further continuation of the previous section.

```

0020
0021 /// Battery parameters calculations
0022 bp.VDC = voltage; // [V]
0023 veh.range = range; // [km]
0024 veh.energyAvg = energy_consumption; // [Wh/km] WLTC
0025
0026 -----
0027
0028 veh.totalEnergyRange = veh.range * veh.energyAvg; // [Wh]
0029
0030 /// Energy density calculations
0031 for i=1:max(size(bc_manufacturer))
0032     bc.energy(i) = bc.capacity(i) * bc.voltage(i); // [Wh]
0033     if [bc_type(i)=='cylindrical']
0034         bc.volume(i) = 1000 * bc.length(i) * (pi*bc.diameter(i)^2/4); //
0035     else
0036         bc.volume(i) = 1000 * bc.height(i) * bc.width(i) * bc.thickness(i)
0037     end
0038     bc.energyDensityMass(i) = bc.energy(i) / bc.mass(i); // [Wh/kg]
0039     bc.energyDensityVolume(i) = bc.energy(i) / bc.volume(i); // [Wh/l]
0040 end
0041 clear i
0042
0043 for i=1:max(size(bc_manufacturer))
0044     bp.noCellsSeries(i) = ceil(bp.VDC / bc.voltage(i)); // [-]
0045     bp.energyString(i) = bp.noCellsSeries(i) * bc.energy(i); // [Wh]
0046     bp.noStrings(i) = ceil(veh.totalEnergyRange / bp.energyString(i)); //
0047     bp.packEnergy(i) = (bp.energyString(i) * bp.noStrings(i))/1000; // [k]
0048     bp.packCapacity(i) = bp.noStrings(i) * bc.capacity(i); // [Ah]
0049     bp.totalCells(i) = bp.noCellsSeries(i) * bp.noStrings(i); // [-]
0050     bp.mass(i) = bc.mass(i) * bp.totalCells(i); // [kg]
0051     if [bc_type(i)=='cylindrical']
0052         bp.stringLength(i) = bp.noCellsSeries(i) * bc.diameter(i); // [m]
0053         bp.stringWidth(i) = bc.diameter(i); // [m]
0054         bp.stringArea(i) = bp.stringLength(i) * bp.stringWidth(i); // [m2]
0055         bp.stringVolume(i) = bp.stringArea(i) * bc.length(i) * 1000; // [l]
0056         bp.packVolume(i) = bp.stringVolume(i) * bp.noStrings(i); // [l]
0057     else
0058         bp.stringLength(i) = bp.noCellsSeries(i) * bc.thickness(i); // [m]
0059         bp.stringWidth(i) = bc.width(i); // [m]
0060         bp.stringArea(i) = bp.stringLength(i) * bp.stringWidth(i); // [m2]
0061         bp.stringVolume(i) = bp.stringArea(i) * bc.height(i) * 1000; // [l]
0062         bp.packVolume(i) = bp.stringVolume(i) * bp.noStrings(i); // [l]
0063     end
0064
0065
0066
0067
0068
0069
0070
0071
0072
0073
    
```

Figure 1. Program for Parameter Calculation

```

0081 /// Plot batt parameters
0082 figure(1)
0083 hf = gcf();
0084 ha = gca();
0085 hf.background = -2;
0086 hf.figure_size = [777,552];
0087 bar(bc.capacity,'black');
0088 ylabel('Battery cell capacity [Ah]', 'FontSize', 2)
0089 ha.x_ticks.labels = bc_manufacturer';
0090 xgrid()
0091 xs2png(hf, 'Battery_cell_capacity.png')
0092
0093 figure(2)
0094 hf = gcf();
0095 ha = gca();
0096 hf.background = -2;
0097 hf.figure_size = [777,552];
0098 bar(bc.voltage,'black');
0099 ylabel('Battery cell voltage [V]', 'FontSize', 2)
0100 ha.x_ticks.labels = bc_manufacturer';
0101 xgrid()
0102 xs2png(hf, 'Battery_cell_voltage.png')
0103
0104 figure(3)
0105 hf = gcf();
0106 ha = gca();
0107 hf.background = -2;
0108 hf.figure_size = [777,552];
0109 bar(bc.energyDensityMass,'black');
0110 ylabel('Energy Density - Gravimetric [Wh/kg]', 'FontSize', 2)
0111 ha.x_ticks.labels = bc_manufacturer';
0112 xgrid()
0113 xs2png(hf, 'Battery_cell_energy_density_gravimetric.png')
0114
0115 figure(4)
0116 hf = gcf();
0117 ha = gca();
0118 hf.background = -2;
0119 hf.figure_size = [777,552];
0120 bar(bc.energyDensityVolume,'black');
0121 ylabel('Energy Density - Volumetric [Wh/l]', 'FontSize', 2)
0122 ha.x_ticks.labels = bc_manufacturer';
0123 xgrid()
0124 xs2png(hf, 'Battery_cell_energy_density_volumetric.png')
0125
    
```

Figure 2. Program for Plotting Battery Parameters

### C. Graph Plotting

Once the program for calculation gets completed the next and final step is of writing the program for generating the graphs. It is processed in two stages: -

- i. For Battery parameters

This will aid to compare all the individual cell parameters such as Voltage, Capacity, Volumetric and Gravimetric energy density. Figure 4 is the screenshot of the Program for Plotting Battery Parameters

- ii. For Pack parameter

This will aid to compare the pack parameters such as no.of cells, Peak current, Peck power, etc. Figure 5 and 6 is the screenshot of the Program for Plotting Pack Parameters

After completing the entire program save the with .sce extension in the same folder where the cell data excel sheet is saved. Later execute the program. Once the program is executed the graphs for the parameters open and the same are saved in the folder as .png files

```

0126 //// Plot pack parameters
0127
0128 figure(5)
0129 hf = gcf();
0130 ha = gca();
0131 hf.background = -2;
0132 hf.figure_size = [777,552];
0133 bar(bp.totalCells,'black');
0134 ylabel('Total number of battery cells [#]', 'FontSize', 2)
0135 ha.x_ticks.labels = bc_manufacturer';
0136 xgrid()
0137 xs2png(hf, 'Total_number_cells.png')
0138
0139 figure(6)
0140 hf = gcf();
0141 ha = gca();
0142 hf.background = -2;
0143 hf.figure_size = [777,552];
0144 bar(bp.mass,'black');
0145 ylabel('Battery pack mass (cells only) [kg]', 'FontSize', 2)
0146 ha.x_ticks.labels = bc_manufacturer';
0147 xgrid()
0148 xs2png(hf, 'Battery_pack_mass.png')
0149
0150 figure(7)
0151 hf = gcf();
0152 ha = gca();
0153 hf.background = -2;
0154 hf.figure_size = [777,552];
0155 bar(bp.packVolume,'black');
0156 ylabel('Battery pack volume (cells only) [l]', 'FontSize', 2)
0157 ha.x_ticks.labels = bc_manufacturer';
0158 xgrid()
0159 xs2png(hf, 'Battery_pack_volume.png')
0160
0161 figure(8)
0162 hf = gcf();
0163 ha = gca();
0164 hf.background = -2;
0165 hf.figure_size = [777,552];
0166 bar(bp.packEnergy,'black');
0167 ylabel('Battery pack energy [kWh]', 'FontSize', 2)
0168 ha.x_ticks.labels = bc_manufacturer';
0169 xgrid()
0170 xs2png(hf, 'Battery_pack_energy.png')
0171

```

Figure 5. Program for Plotting Pack Parameters

```

0172 figure(9)
0173 hf = gcf();
0174 ha = gca();
0175 hf.background = -2;
0176 hf.figure_size = [777,552];
0177 bar(bp.packCapacity,'black');
0178 ylabel('Battery pack capacity [Ah]', 'FontSize', 2)
0179 ha.x_ticks.labels = bc_manufacturer';
0180 xgrid()
0181 xs2png(hf, 'Battery_pack_capacity.png')
0182
0183 figure(10)
0184 hf = gcf();
0185 ha = gca();
0186 hf.background = -2;
0187 hf.figure_size = [777,552];
0188 bar(bp.packPeakCurrent,'black');
0189 ylabel('Battery pack peak current [A]', 'FontSize', 2)
0190 ha.x_ticks.labels = bc_manufacturer';
0191 xgrid()
0192 xs2png(hf, 'Battery_pack_peak_current.png')
0193
0194 figure(11)
0195 hf = gcf();
0196 ha = gca();
0197 hf.background = -2;
0198 hf.figure_size = [777,552];
0199 bar(bp.packPeakPower,'black');
0200 ylabel('Battery pack peak power [kW]', 'FontSize', 2)
0201 ha.x_ticks.labels = bc_manufacturer';
0202 xgrid()
0203 xs2png(hf, 'Battery_pack_peak_power.png')
0204
0205 figure(12)
0206 hf = gcf();
0207 ha = gca();
0208 hf.background = -2;
0209 hf.figure_size = [777,552];
0210 bar(bp.packContCurrent,'black');
0211 ylabel('Battery pack continuous current [A]', 'FontSize', 2)
0212 ha.x_ticks.labels = bc_manufacturer';
0213 xgrid()
0214 xs2png(hf, 'Battery_pack_cont_current.png')
0215
0216 figure(13)
0217 hf = gcf();
0218 ha = gca();
0219 hf.background = -2;
0220 hf.figure_size = [777,552];
0221 bar(bp.packContPower,'black');
0222 ylabel('Battery pack continuous power [kW]', 'FontSize', 2)
0223 ha.x_ticks.labels = bc_manufacturer';
0224 xgrid()
0225 xs2png(hf, 'Battery_pack_cont_power.png')
0226
0227 disp('done')

```

Figure 6. Program for Plotting Pack Parameters

## 6. Results

By using Scilab the graphs for comparing the battery cells are generated. By analyzing the graphs, the suitable cell can be selected accordingly. Below is the result of the battery cells:

i. Battery Cell Capacity




Fig 7. Battery Cell Capacity

ii. Battery Cell Voltages




Fig 8. Battery Cell Voltages

iii. Energy Density – Gravimetric




Fig 9. Energy Density – Gravimetric

iv. Energy Density – Volumetric




Fig 10. Energy Density – Volumetric

v. Battery Pack Capacity




Fig 11. Battery Pack Capacity

vi. Battery Pack Continuous Current




Fig 12. Battery Pack Continuous Current

vii. Battery Pack Continuous Power




Fig 13. Battery Pack Continuous Power

viii. Battery Pack Energy




Fig 14. Battery Pack Energy

ix. Battery Pack Peak Current




Fig 15. Battery Pack Peak Current

x. Battery Pack Peak Power




Fig 16. Battery Pack Peak Power

xi. Battery Pack Volume




Fig 17. Battery Pack Volume

xii. Battery Pack Mass




Fig 18. Battery Pack Mass

xiii. Total Number of Cells




Fig 19. Total Number of Cells

An electric vehicle needs a good amount of acceleration and power to cruise at a constant speed so the battery pack should have a good continuous current and peak current. While a battery pack should be compact and lightweight. Thus, it should have high gravimetric and volumetric energy. By analyzing the graphs, the cell which provides a better combination of the tradeoffs can be selected.

## 7. Conclusions

The prime focus of the paper was on the comparison of different battery cells the application of electric vehicle battery packs. With the help of Scilab, the comparison was carried out by writing and executing the required programs for generating the graphs for the battery cell comparison. This method can be used for the comparison of any number of cells and parameters for a varied range of applications. The formulas and the method used for comparison are basic and easy to understand. Though this method does not elaborate on the state of charge of the battery. Yet, it can be effectively used for the primary stage of battery cell selection.

## References

### Electronic Journals

- [1] Modelling and Evaluation of Battery Packs with Different Numbers of Paralleled Cells by Fengqi Chang, Felix Roemer, Michael Baumann and Markus Lienkamp.2018. MDPI <https://www.mdpi.com/2032-6653/9/1/8>

- [2] Batteries for Electric Vehicles by Dr. K.V. Vidyanandan. 2019.Researchgate  
[https://www.researchgate.net/publication/337337281\\_Batteries\\_for\\_Electric\\_Vehicles](https://www.researchgate.net/publication/337337281_Batteries_for_Electric_Vehicles)
- [3] A Review on Battery Modelling Techniques by S. Tamilselvi 1, S. Gunasundari, N. Karuppiyah et al.2021.MDPI  
[https://www.mdpi.com/2071-1050/13/18/10042?type=check\\_update&version=2](https://www.mdpi.com/2071-1050/13/18/10042?type=check_update&version=2)
- [4] Mathematical Modeling of the Electric Scooter Battery Pack Using Scilab by Hrushikesh Chari and Dr.R.S.Katkar.2022.IJARIIT  
<https://www.ijariit.com/manuscript/mathematical-modeling-of-the-electric-scooter-battery-pack-using-scilab/>

**Websites**

- [5] <https://www.pveducation.org/pvcdrom/batteries/battery-characteristics>
- [6] [https://afdc.energy.gov/vehicles/electric\\_batteries.html](https://afdc.energy.gov/vehicles/electric_batteries.html)